FM10Q, 10.4-inch Vehicle Mounted Computer

A Rugged Vehicle Mounted Computer for Data Collection in Warehouse and Logistics Applications

The FM10Q is an Android-based rugged vehicle-mounted computer that ships with a high performance Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz CPU. The computer showcases enterprise mobility in a VMC form factor thanks to its rich I/O ports, versatile wireless connectivity options, as well as the high flexibility brought by the design of the dock with a one-click top latch, which allows for easy removal of the device. Engineered to fit seamlessly into forklifts and other warehouse vehicles with its wide range of power input with power isolation, the FM10Q will help minimize errors, streamline inventory management, and improve operational efficiencies.









Highlights

- Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz CPU
- 10.4" 1024 x 768 Panel with PCAP touchscreen
- Field replaceable front panel to reduce service costs
- · Magnesium alloy housing
- Built-in Wi-Fi and BT
- IP65 waterproof and dustproof
- Wide range -30°C to 50°C operating temperature

Order Information			
Model Number	4G	High Brightness Panel	Heater
FM10Q	N/A	N/A	N/A
FM10Q-LA	4G LTE	N/A	N/A
FM10Q-HB	N/A	Yes	N/A
FM10Q-LAHB	4G LTE	Yes	N/A
FM10Q-T	N/A	N/A	Yes
FM10Q-LAT	4G LTE	N/A	Yes
FM10Q-HBT	N/A	Yes	Yes
FM10Q-LAHBT	4G LTE	Yes	Yes

^{*}Brightness will be reduced if the heater is added.



FM10Q, 10.4-inch Vehicle Mounted Computer

A Rugged Vehicle Mounted Computer for Data Collection in Warehouse and Logistics Applications

Display Specification

10.4-inch display (4:3) Size Resolution 1024 x 768

Brightness 400 nits (Optional 800 nits)

Touch Projected capacitive (PCAP) multi-touch

Contrast Ratio Viewing Angle 88/88/88/88

Sensor G-Sensor •Temp. Sensor

System Specification

Processor Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz

3GB LPDDR4 System Memory 32GB eMMC Storage

Additional storage with Micro SD card slot

Operating System Android 9.0

Wireless Communication

WLAN 802.11 a/b/g/n/ac

ВТ

GNSS GPS module on Docking

Optional 4G LTE WWAN

Interface

1 x Dual-Nano SIM Card Slot Computer

1 x Micro SD Card Slot 1 x USB 3.0 Type C (OTG) 1 x 12V DC in power input jack

Docking

1 x DB9 Connector for 2 x USB 2.0 Port 1 x CANBus or 1 x Audio (In and Out)²

1 x Gigabit LAN port 1 x Power connector

5 x SMA Connectors (Female) for external antennas

(WLAN, GPS, WWAN)

Input

Touch 10-point PCAP multi-touch, with stylus support

Physical Buttons 1 x Power, 6 x Function kevs

(Programmable function key configured by Winset)

Status Indicators

LED Indicators Wi-Fi, Bluetooth, UPS battery, HDD,

Screen Blanking, Heater 3

Audio

Speaker 2 x 3W speaker on docking

Cameras

Front Camera • 2MP webcam

· Reading Light

Security Function

Mobile Device Management SOTI Mobicontrol compatible 4



Do Not Expose the Battery Pack to Excessive Heat, or Extreme Heat (Near Fire, in Direct Sunlight for example)

Do not expose bare skin to this product when handling this unit in extreme hot or cold environments

- 1. Total usable memory will be less depending upon actual system configuration.
- 2. CANBus and audio are mutually exclusive
- Heater is a customized feature available by request
- 4. SOTI is available upon request
- 5. Length measurements do not include protrusions. Weight varies with options.

Mechanical

Computer: 268 x 214 x 35 mm (10.6 x 8.42 x 1.37 inches) 5 Dimension (W x L x H)

Docking: 202 x 245 x 52 mm (7.9 x 9.6 x 2.04 inches)

Computer 1.7 kg (3.75 lbs) Docking 1.6 kg (3.53 lbs) Magnesium alloy housing Housing

Cooling System Fanless design

Environment

Operating Temperature -30°C to +50°C (-22°F to +122°F) -30°C to +50°C (-22°F to +122°F) Storage Temperature Humidity 5% to 90% RH, non-condensing IP Proof IP65 certified, dustproof and waterproof Support EN62262 IK70 rating Impact MIL-STD-810G Method 516.6 Procedure I Shock Vibration MIL-STD-810G Method 514.6 Procedure I **ESD**

Compliant with EN 61000-4-2,

enhanced ESD to ±8kV direct & ±15kV air

Power Management

Docking Power Input 10V-60V with power isolation and ignition control 12V DC in

Tablet Power Input

Battery Integrated Li-Ion maintenance UPS with 30-min life at 0°C (32°F)

Accessories 7


Standard Accessories

Power Cable with Fuse 98K000A0006O 84 Watt Adapter 922D084W12V1 Power Converter Cable 94J602G030K2 USB Cable 9483098080K0 39700000000G Wi-Fi Antenna External Antenna Fixing Bracket 9 88111T201203 Quick Start Guide 9152111I102W Stylus Kit 98K000A00076 Power Cord Country Specific P/Ns

Optional Accessories

DC Power Jack Cable 94J0086020K0 RS232 Cable 94G3094090K2 Audio Cable 94E215R060K0 CANBus Cable 94E2150090K0 CANBus cable (w/o DIDO) 94E215L030K0 LAN Cable 94I0080080KF Key for Vehicle Dock 9B00000007N WWAN Antenna 39700000000H Fuse Kit 94JL01L01000

Drawing 11







- 6. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached
- Accessories may vary depending on your configuration
- 8. Two Wi-Fi antennas are included in the standard package
- 9. Please order one bracket for one antenna. For example, if you plan to use two antennas, please order two brackets
- 10. Notice that only one antenna is included in the package. If you plan to use WWAN function please order two WWAN antennas.
- 11. This is a simplified drawing and some components are not marked in detail.



Release Date: 30-Sep-2020 V2.6